## Amendments to the Claims: 1 2 This listing of claims will replace all prior versions, and listings of claims in the applications: 3 **Listing of Claims:** 4 I claim: 5 1. (Currently Amended) A syringe needle de-capping and re-capping device, comprising: 6 a. a cylindrical shaped body with longitudinally aligned cavity formed therein; said 7 body including a finger gripping section; 8 b. a removable cap selectively attachable to said body, said cap including an inward 9 extending aligned neck; c. a bushing longitudinally aligned and located inside said cavity, said bushing 10 11 including a cylindrical shaped void area capable of receiving said neck on said removable 12 cap, said bushing includes a stop surface formed inside said void area; and; d. a spring nut located inside said void area of said bushing, said spring nut including 13 14 a center bore that engages the tip of a needle cap with inserted therein; and, 15 2. (Currently Amended) The syringe needle de-capping and re-capping device, as recited in 16 17 Claim 1, wherein said finger gripping gripping member that allows said body to be held 18 between a user's finger so that said cavity is located above the top surface of the user's 19 fingers. 20 The syringe needle de-capping and re-capping device as recited in Claim 2, 21 3. (Original) wherein said body and said finger gripping member are longitudinally aligned so that when a 22 user's fingers engage said finger gripping member, said cylindrical body extends upward 23

1	substantially perpendicular to the top surface of the fingers used to hold said device.			
2				
3	4. (Original) The syringe needle de-capping and re-capping device, as recited in Claim 1,			
4	wherein said bushing is made of radiation shielding material.			
5				
6	5. (Original) The syringe needle de-capping and re-capping device, as recited in Claim 2,			
7	wherein said bushing is made of radiation shielding material.			
8				
9	6. (Original) The syringe needle de-capping and re-capping, as recited in Claim 3, wherein			
10	said bushing is made of radiation shielding material.			
11				
12	7. (Original) The syringe needle de-capping and re-capping device as recited in Claim 1,			
13	wherein said body and said finger gripping member are made of molded rubber.			
14				
15	8. (Currently Amended) The syringe needle de-capping and re-capping device as recited in			
16	Claim 1, further including a ring attached to said body having internal threads formed on said			
17	cavity and said cap including external threads that selectively interconnect to attached said			
18	cap to said body.			
19				
20	9. (Original) The syringe needle de-capping and re-capping device as recited in Claim 1,			
21	wherein said neck is an adaptor removably attached to said cap.			
22				
23	10. (Currently Amended) The syringe needle de-capping and re-capping eapping device, as			

1	recited in Claim 9, further including a bushing made of
2	radiation shielding material.
3	
4	11. (Original) The syringe needle de-capping and re-capping device as recited in Claim 1,
5	wherein said body and said finger gripping member are perpendicularly aligned so that when
6	a user's fingers engage said finger gripping member, said cylindrical body extends
7	transversely over the top surface of the user's fingers.
8	
9	12. (Original) The syringe needle de-capping and re-capping device, as recited in Claim 11,
10	wherein said bushing is made of radiation shielding material.
11	
12	13. (Original) The syringe needle de-capping and re-capping device, as recited in Claim 1,
13	when said finger gripping member is conical.
14	
15	14. (Currently Amended) A syringe needle de-capping and re-capping device, comprising:
16	a. a cylindrical body with longitudinally aligned bushing cavity formed therein;
17	b. a t-shaped finger griping member longitudinally aligned and formed on said body
18	capable of being engaged between two fingers on a user's hand;
19	c. a removable cap attached to said cylindrical body to selectively close said cavity,
20	said removable cap including a small opening capable of receiving a needle cap;
21	d. a bushing located inside said cavity formed in said body; _said bushing including a
22	void area; and,
23	e. a spring nut located inside said void area of said bushing capable to engaging the

1	tip of a needle cap when inserted through said small opening on said removable cap and into		
2	said void area in said bushing.		
3			
4	15. (Currently Amended) The syringe needle de-capping and re-capping device, as recited		
5	in Claim 14, wherein said bushing is made of a radiation shielding material.		
6			
7	16. (Currently Amended) The syringe needle de-capping and re-capping device as recited in		
8	Claim 14, further including an adapter attached to said cap that extends into said bushing to		
9	hold said spring nut inside said bushing.		
10			
11	17. (Currently Amended) The syringe needle de-capping and re-capping device, as recited		
12	in Claim 16, wherein said bushing is made of radiation shielding material.		
13			
14	18. (Currently Amended) A syringe needle de-capping and re-capping device, comprising:		
15	a. a cylindrical body with longitudinally aligned cavity formed therein;		
16	b. a t-shaped finger gripping member located on one side of said body		
17	capable of being engaged between two fingers on a user's hand;		
18	c. a removable cap attached to said body to selectively close said cavity, said		
19	removable cap including a small opening capable of receiving a needle cap;		
20	d. a bushing located inside said cavity formed in said body said bushing including a		
21	void area; and,		
22	e. a spring nut located inside said void area of said bushing capable to engaging the		

tip of a needle cap when inserted through said small opening on said removable cap and into

1	said void area in said bushing.		
2			
3	19. (Currently Amended)	The syringe needle de-capping and re-capping eapping device, as	
4	recited in Claim 18, where	in said bushing is made of radiation material.	
5			
6	20. (Currently Amended)	The syringe needle de-capping and re-capping device, as recited	
7	in Claim 18, wherein said	bushing is made of radiation shielding material.	
8			
9			
10			
11			
12			
13		· · · · · · · · · · · · · · · · · · ·	
14			
15			
16			
17			
18			
19			
20			
21			
22			